

BAIYILED GKU LED High-Bay luminaries

GKU Series 100W/150W

Product Features

Enjoy savings up to 70% and zero maintenance without compromising on brightness or light quality.

Designed as a replacement for HPI 250/400W luminaries, Baiyiled GKU High-Bay offers customers all the benefits of LED lighting— instant on and off, excellent light quality, longer lifetime, and reduced energy consumption and maintenance.

GKU High-Bay is equipped with top quality Lumiled LED chip, Meanwell driver, offering different light distribution angel. It has been certified by CE, RoHS, LM79, etc. It has also been tested by many other European institutes and labs with excellent results.



Applications

Manufacturing
Warehouse
Distribution-center
Logistic center

Parameters

Lifespan	50000H
Rated power	100W / 150W
Voltage	AC 90-264V Hz50/Hz60
Lamp size	320 x 143 mm
Beam angle	40° / 75° / 105°
CRI	≥80
Color temperature	3000K/4000K/5000K/6500K
Luminous flux	100W 13000lm 150W 19500lm
Working environment	-30°C~55°C
Protection rate	IP65
Power factor	>0.98
Dimmable	Optional : 1-10v Dimming

2500k 4000k 7500k



BAIYILED

BAIYILED EUROPE B.V.
Koningsbeltweg 72A
1329AK Almere
The Netherlands

Email : Info@baiyiled.nl
Tel : +31 (0)36 7850321
Website: www.baiyiled.nl