

BAIYILED TGC LED Floodlight

TGC Series 120W

Product Features

Enjoy savings up to 70% and zero maintenance without compromising on brightness or light quality.

BAIYILED TGC LED floodlight was designed specifically to replace conventional lighting in a wide variety of industrial applications for both indoor and outdoor.

The TGC fixture has a small profile and light weight, it is ideal for many applications such as indoor and outdoor car parks, garages, cold storage and general area lighting applications with mounting heights 4 - 6 meters.

Working perfectly on AC110 volt makes TGC floodlight also an excellent choice for outdoor temporary lighting such as tower lighting.

TGC floodlight offers customers all the benefits of LED lighting— instant on and off, excellent light quality, longer lifetime, and reduced energy consumption and maintenance.

It is equipped with top quality BridgeLux LED chip, optical lens and it has been certified by CE, RoHS, LM79, etc. TGC LED floodlight has also been tested by many other European institutes and labs with excellent results.






Applications

- Manufacturing
- Warehouse
- Distribution-center
- Temporary site
- Tower lighting
- Cold storage
- Garages

Parameters

Lifespan	50000H
Rated power	120W
Voltage	AC 90-264V Hz50/Hz60
Lamp size	Φ366 x 155 mm
Beam angle	105°
CRI	≥80
Color temperature	3000K/4000K/5000K/6500K
Luminous flux	13200lm
Working environment	-30°C~50°C
Protection rate	IP65
Power factor	>0.98
Power efficiency	>87%
Dimmable	Nope



BAIYILED

BAIYILED EUROPE B.V.
Koningsbeltweg 72A
1329AK Almere
The Netherlands

Email : Info@baiyiled.nl
Tel : +31 (0)36 7850321
Website: www.baiyiled.nl