



SCHOOL



INDUSTRY



WAREHOUSE



SWIMMING POOL



SUPERMARKET



SPORTS HALL




FOOD PROCESSING



PRODUCTION HALL

TRITON LED BULKHEAD

SERIES 5W



DESCRIPTION

The Triton LED Bulkhead is a powerful luminaire for many applications. The Triton is built with durable PMMA for its housing and is equipped with premium components and LED chips. This allows the Triton to have a lifespan over 30,000 hours without it requiring any maintenance and save up to 70% on energy costs.

The Triton is designed to easily replace conventional fluorescent fixtures in apartment buildings, flats and other buildings. The fixture can therefore be Plug & Play installed. The Triton is IP65 certificated allowing it to be installed in -or outdoor and is available with a transparent or milky cover, which reduces its glare and increases visual comfort.

The Triton luminaire is available with built in emergency module which comes with the innovative self-testing function. It will test the emergency module 3x per year and show the status with the colored LED indicators.

OPTIONAL

- Emergency Module (90min/180min)

OTHER APPLICATIONS

- Shopping Mall
- Buildings
- House/Apt. Building
- Airport
- Logistic Center

BAIYILED



This luminaire contains built-in LED lamps.



LED

The lamps cannot be changed in the luminaire.

874/2012



TRITON LED BULKHEAD

SERIES 5W

PRODUCT DETAIL

PRODUCT CODE	PRODUCT DESCRIPTION	POWER (W)	LUMEN	EFFICIENCY (LM/W)	CCT (K)	CRI	DIMENSIONS L X W X H (MM)	REPLACEMENT FOR	LIFESPAN L80 AT 25°C
BY-PTL-5W	Triton LED Bulkhead 5W	5	500	100	3000 / 4000 / 6500	>80	346 x 107 x 60	1 x 8w FL	30,000H
BY-PTL-EPS5W	Triton LED Bulkhead 5W With Emergency	5	500	100	3000 / 4000 / 6500	>80	346 x 107 x 60	1 x 8w FL	30,000H

SPECIFICATIONS AND DETAILS

TECHNICAL SPECIFICATIONS

Dimmable	No
Beam Angle	120°
IP Rating	IP65
Protection Class	I
Integrated Driver	Yes

ELECTRICAL SUPPLY

Voltage (V)	220 - 240
Frequency (Hz)	50 / 60
AC/DC	AC
Power Factor	>0.90
THD	<15

MATERIALS

Housing	PMMA
Colour (Housing)	White
Lens	Milky Polycarbonate Diffuser

APPLICATION

Operating Temperature	-20°C ~ 45°C
-----------------------	--------------

PROPERTIES OF OPTIONAL ITEMS

Emergency	Integrated Module (90min/180min)
-----------	----------------------------------

DIMENSIONAL DRAWINGS

